

ACRYLOC® PREMIUM TRADELINE SUPER FLAT

PRODUCT TYPE

Premium Interiors

PACKAGING

4L 10L Steel Cans, 15L Plastic Pail

NOMINAL WEIGHT

6kg, 15kg, 22kg respectively

DESCRIPTION

Acryloc *Premium Tradeline Super Flat* is a professional quality, low odour, flat finish coating, suitable for all interior ceilings and for exterior eave linings, portico & veranda ceilings, including areas normally susceptible to mould/mildew.

Acryloc *Premium Tradeline Super Flat* is formulated to give high hiding power, easy touch up and low spatter.

FEATURES & BENEFITS

- Excellent water resistance
- Excellent vapour permeability
- Low Odour
- High hiding power
- Easy to apply, low spatter formula
- Water based, Easy & safe clean up

SUBSTRATE PREPARATION

- Areas not to be coated should be masked and protected

New Unpainted Surfaces

Fill nail holes, cracks and imperfections with an appropriate patching material and sand smooth.

Remove dust and make sure that the surface is clean, sound and free from contaminants such as oil, mould release, silicone, grease and efflorescence.

Paperfaced Wallboard, Masonry, Cement, Brick:

Apply one coat of Primerbond Wallboard Sealer or Ultra PSU.

Bare Timber or MDF:

Apply one coat of Primerbond All Purp Undercoat.

Fibrous or Set Plaster:

Apply one coat of Primerbond Wallboard Sealer. A second coat may be required on very porous surfaces.

Ultra PSU may also be used.

Previously painted surfaces

Wash down with sugar soap and rinse with clean water.

Check for soundness of the original coating, remove any loose or flaking paint, fill holes and cracks and sand to an even finish.

Gloss or Semi-Gloss finishes must be completely dulled by sanding.

Spot prime bare areas as recommended for new surfaces above.

Apply one coat of Primerbond All Purp Undercoat.

Important Notes

- Application should be carried out on a day with temperatures above 10°C and below 32°C.

APPLICATION

- Thinning is not normally required but up to 100mL of clean water per litre of paint can be added to the first coat when spraying or in warm conditions.
- Acryloc Extenda is recommended in warm conditions to assist in maintaining a 'wet edge'; add up to 30mL per Litre.
- Mix thoroughly and check that the colour (if tinted) is correct before commencing work.
- Apply one full even coat of Acryloc *Premium Tradeline Super Flat* by brush, spray or roller.
- For Roller application, a medium nap (12mm) roller is recommended. High quality synthetic rollers give best performance. Use a 13 or 15 thou spray tip with Airless spray.
- Allow minimum 2 hours to dry and apply a Second coat.

Clean-Up

- Clean up with water

OTHER CONSIDERATIONS**Shelf-Life – Unopened Containers**

Maximum two (2) years from date of manufacture when stored correctly

Transport & Storage

Pails should not be stacked more than three (3) high during transportation and must be transported upright

Store in a cool place, upright, out of direct sunlight and above 4°C

For further information refer to **MSDS** for *Acryloc Premium Tradeline Super Flat*

TECHNICAL DATA

| | | | |
|--------------------------------------|-----------------------------------|------------------|-------------|
| APPEARANCE | Viscous white liquid | | |
| ODOUR | Low | | |
| APPLICATION METHODS | Roller, brush, spray | | |
| SPECIFIC GRAVITY (NOMINAL) | 1.4 -1.6 | | |
| THEORETICAL COVERAGE | 12 - 15m ² /L per coat | | |
| DRY TIME (25°C & 50% RH) (APPROX) | Tack Free | Recoat/ Overcoat | Fully Dried |
| | 1 hour | 2 hours | 48 hours |
| NO. OF COATS | 2 | | |
| GLOSS LEVEL | Flat | | |

SAFETY & HANDLING

Refer to **MSDS** for *Acryloc Premium Tradeline Super Flat* before use. For further information on Material Safety Data Sheets, call the Acryloc Tech – Info line on 1300 661 745 or visit www.acryloc.com.au

When working with *Acryloc Premium Tradeline Super Flat* observe the usual precautions for handling acrylic water based products including:

- Avoid inhalation of the vapour, prolonged skin contact and particularly eye contact
- Wear protective clothing to minimize skin contact and wear goggles where splatter is likely
- Where spills occur, soak up liquid spillage with sand/sawdust and dispose of in a sensible manner. Do not permit run-off to sewer, storm water or open bodies of water

Full pails are HEAVY. Wear protective footwear and seek assistance if necessary.

FIRST AID MEASURES

Refer to **MSDS** for *Acryloc Premium Tradeline Super Flat* before use. For further information on Material Safety Data Sheets, call the Acryloc Tech – Info line on 1300 661 745 or visit www.acryloc.com.au

If swallowed, wash out mouth with water. Do **NOT** induce vomiting. Drink at least two (2) glasses of water. Seek medical attention.

Eye

Wash with copious amount of water for 15 minutes holding eyelid(s) open. Take care not to rinse contaminated water into non-affected eye. Seek medical attention.

Advice to Doctor

Treat symptomatically

MANUFACTURED BY:

Bizfine Pty Ltd

T/A Acryloc Building Products

174 Cavan Rd

DRY CREEK

South Australia 5094

P: +61 8 8368 0222

F: +61 8 8368 0223

E: sales@acryloc.com.au

W: www.acryloc.com.au

