



weatherblock®



- All weather protection for your home
- Water based, Low Sheen or Satin
- Available in a range of fashionable colours

**Proudly Australian Owned & Operated**

manufactured by  
**acryloc**<sup>®</sup>  
building products



weatherblock®

Weatherblock helps protect your home from the extremes of Australian weather conditions.

It is water based, easy to apply and suitable for most surfaces.

Weatherblock has a 15 year guarantee against flaking, blistering and peeling.

Weatherblock is made right here in Australia using only the highest quality ingredients available.



- 36 Tint Pac colours, including colours to match Colorbond®
- Selected Resellers can also match a wide range of competitor colours
- Available in Low Sheen and Satin finishes and in 5 Litre, 10 Litre and 15 Litre pails
- No primer required on most surfaces\*
- High quality pigments for maximum UV protection and resistance to fading
- Tough yet flexible to resist cracking
- Resistant to mould and algae growth
- Low odour formulation
- Water based for safe and easy cleanup



*Durability testing in our laboratory.*

---

#### How much do I need?

Weatherblock covers up to 16 square meters per Litre, depending on the surface and application method. That means a 5 Litre pail will give the recommended two coats for up to 40 square metres. You will need more for rough or porous surfaces.

#### What can I paint with it?

Use Weatherblock for walls, sheds, pergolas, tanks, fences & more and on a wide range of surfaces including dressed and rough sawn timber, fibre cement sheeting, bricks and masonry, plastic, steel, Zinalume® and galvanised iron. Ideal for planter pots, trims, facias and downpipes.

#### How long till it is dry?

Touch Dry in 20 minutes, Recoat after 2 hours. This is for normal conditions on a day of around 25°C; times may be longer if it is cold and/or humid, shorter if it is warm and/or dry.

\* Weatherblock is self priming on most surfaces. Exceptions are steel & wrought iron. Also Zinalume® and galvanised iron within 1km of the sea. In these cases apply Primerbond Metal & Galv first.

© Acryloc, Weatherblock and Reflectacoat are registered trademarks of Acryloc Building Products.  
© Zinalume and Colorbond are a registered trademark of Bluescope Steel Ltd.

#### How do I put it on?

Apply two generous coats of Weatherblock Exterior Acrylic with a brush, 12mm synthetic roller or spray. Thinning is not normally required but up to 100mL of clean water per litre of paint can be added to the first coat when spraying, in warm conditions or on rough sawn timber and other very porous surfaces.

#### What else do I need to know?

Paint will not stick to a surface that is dirty. Make sure the surface is clean, sound and free from contaminants as well as loose or flaking material. The temperature must be above 10°C during application and drying. If all else fails, detailed instructions are on the label.

**acryloc**®  
building products

174 Cavan Road Dry Creek SA  
P +61 8 8368 0222  
E sales@acryloc.com.au  
W www.acryloc.com.au

#### Who is Acryloc?

A proudly Australian Owned & Operated company. We have been making water based exterior paints for over 20 years and our products are in use throughout Australia. We also export to a number of overseas markets. Weatherblock Exterior Acrylic is made in our Adelaide factory.

---