

## ACRYLOC® PRIMERBOND ROOF RECOAT

**PRODUCT TYPE**  
Primers & Undercoats

**PACKAGING**  
15L Heavy Duty Plastic Pail

**NOMINAL WEIGHT**  
17kg

### DESCRIPTION

Acryloc *Primerbond Roof Recoat* is a ready to use, clear drying, penetrating and binding primer.

Acryloc *Primerbond Roof Recoat* is the recommended primer for previously painted roofs as part of the Roofcote System. The formulation is designed to penetrate and bind the surface and provide a 'key' for subsequent coats.

Note that the existing coating must be sound.

Acryloc *Primerbond Roof Recoat* is not able to rectify cracking, peeling or blistering of the previous coating.

Where the previous coating is not sound it must be completely removed before proceeding.

### FEATURES & BENEFITS

- Excellent Binding properties
- Excellent flexibility
- Strong adhesion to previously painted surfaces
- Water based for Easy & Safe clean up

### SUITABLE SUBSTRATES

- Previously painted roofs

### SUBSTRATE PREPARATION

- Areas not to be coated should be masked and protected
- All surfaces to be coated must be clean, sound, free from contaminants including: oil, mould release, dust, dirt, silicone, mud, grease, salt, efflorescence, animal droppings and any loose or flaking material
- Application of Acryloc Mould Rid prior to priming will inhibit growth of moss & lichen.
- Care should be taken to keep Acryloc *Primerbond Roof Recoat* off windows and adjacent surfaces that are not to be coated, as it can be very difficult to remove once allowed to dry

### APPLICATION

- Acryloc *Primerbond Roof Recoat* does not require thinning or dilution
- Mix thoroughly with a broad, flat stirrer, using an upward lifting action
- Acryloc *Primerbond Roof Recoat* can be applied using HVLP or airless spray equipment
- If using spray equipment, a 17 or 19 thou tip and white gun filter is recommended
- Apply Acryloc *Primerbond Roof Recoat* liberally, completely covering the surface. Applying excess material is acceptable providing it is not allowed to pool on the surface, as this may affect the top coat.
- *Primerbond Roof Recoat* must be over-coated with an appropriate product from the coating system being used

### Important Notes

- Do not apply Acryloc *Primerbond Roof Recoat* on exposed surfaces when rain is anticipated within 5 hours of completion of the work, longer in damp, cold +/- humid conditions
- Avoid application on hot surfaces or in hot &/or windy conditions.
- Application should be carried out on a day with temperatures above 10°C and below 32°C
- Coated area must be protected from damage until the completion of the project; finished work must be protected from rain, frost and severe weather conditions until fully dried

**OTHER CONSIDERATIONS****Clean-Up**

Clean up with water

**Shelf-Life – Unopened Containers**

Maximum two (2) years from date of manufacture when stored correctly.

**Transport & Storage**

Pails should not be stacked more than three (3) high during transportation and must be transported upright

Store in a cool place, upright, out of direct sunlight and above 4°C

For further information refer to **Safety Data Sheet (SDS)** for Acryloc Primerbond Roof Restore**TECHNICAL DATA**

APPEARANCE	Milky white liquid		
ODOUR	Low		
APPLICATION METHODS	Roller, brush, spray		
SPECIFIC GRAVITY (NOMINAL)	~1.1		
THEORETICAL COVERAGE	12-14m <sup>2</sup> /L per coat on roofs		
DRY TIME (25°C & 50% RH) (APPROX)	Tack Free	Recoat/ Overcoat	Fully Dried
	60 mins	After 90	N/A
NO. OF COATS	Typically 1 coat		

**SAFETY & HANDLING**For further information refer to **Safety Data Sheet (SDS)** for *Acryloc Primerbond Roof Recoat*, call the Acryloc Tech – Info line on 1300 661 745 or visit [www.acryloc.com.au](http://www.acryloc.com.au)When working with *Acryloc Primerbond Roof Recoat* observe the usual precautions for handling acrylic water based products including:

- Avoid inhalation of the vapour, prolonged skin contact and particularly eye contact
- Wear protective clothing to minimize skin contact and wear goggles where splatter is likely
- Where spills occur, soak up liquid spillage with sand/sawdust and dispose of in a sensible manner. Do not permit run-off to sewer, storm water or open bodies of water

Full pails are HEAVY. Wear protective footwear and seek assistance if necessary.

**FIRST AID MEASURES**For further information refer to **Safety Data Sheet (SDS)** for *Acryloc Primerbond Roof Recoat* before use. For further information on Material Safety Data Sheets, call the Acryloc Tech – Info line on 1300 661 745 or visit [www.acryloc.com.au](http://www.acryloc.com.au)**Ingestion**If swallowed, wash out mouth with water. Do **NOT** induce vomiting. Drink at least two (2) glasses of water. Seek medical attention.**Eye**

Wash with copious amount of water for 15 minutes holding eyelid(s) open. Take care not to rinse contaminated water into non-affected eye. Seek medical attention.

**Advice to Doctor**

Treat symptomatically

**MANUFACTURED BY:**

Bizfine Pty Ltd  
T/A Acryloc Building Products  
174 Cavan Rd  
DRY CREEK  
South Australia 5094  
P: +61 8 8368 0222  
F: +61 8 8368 0223

E: [sales@acryloc.com.au](mailto:sales@acryloc.com.au)W: [www.acryloc.com.au](http://www.acryloc.com.au)