

ACRYLOC® PRIMERBOND ROOF RESTORE

PRODUCT TYPE
Primers & Undercoats

PACKAGING
15L Heavy Duty Plastic Pail

NOMINAL WEIGHT
16.5kg

DESCRIPTION

Acryloc *Primerbond Roof Restore* is the main primer for the Roofcote CRC and Roofcote Supa Cool systems, recommended for use on most roof tiles, aged Colorbond® and fibre cement surfaces.

Acryloc *Primerbond Roof Restore* is a clear drying, water based, penetrating and binding acrylic primer and is extremely effective on a wide range of substrates, particularly where the surface is chalky or prone to dusting.

The formulation is designed to penetrate and bind the surface and provide a 'key' for subsequent coats.

FEATURES & BENEFITS

- Excellent Binding properties
- Excellent flexibility
- Strong adhesion to a range of substrates
- Water based for Easy & Safe clean up

SUITABLE SUBSTRATES

- Pre-cleaned concrete roof tiles
- Pre-cleaned unglazed terracotta roof tiles
- Aged Colorbond®
- Tilt panel walls
- Clay and Concrete Brickwork
- Cement Render & other rendered surfaces
- AAC (Autoclaved Aerated Concrete)
- Fibre Cement Sheeting

SUBSTRATE PREPARATION

- Areas not to be coated should be masked and protected
- All surfaces to be coated must be clean, sound, free from contaminants including; oil, mould release, dust, dirt, silicone, mud, grease, salt, efflorescence, animal droppings and any loose or flaking material
- Application of Acryloc Mould Rid prior to priming will inhibit growth of moss & lichen.
- Care should be taken to keep Acryloc *Primerbond Roof Restore* off windows and adjacent surfaces that are not to be coated, as it can be very difficult to remove once allowed to dry

APPLICATION

- Acryloc *Primerbond Roof Restore* does not require thinning or dilution
- Mix thoroughly with a broad, flat stirrer, using an upward lifting action
- Acryloc *Primerbond Roof Restore* can be applied using HVLP or airless spray equipment
- If using spray equipment, a 17 or 19 thou tip and white gun filter is recommended
- Apply Acryloc *Primerbond Roof Restore* liberally, allowing good penetration into the substrate. Applying excess material is acceptable providing it is not allowed to pool on the surface, as this may affect the top coat.
- *Primerbond Roof Restore* must be over-coated with an appropriate product from the coating system being used

Important Notes

- Do not apply Acryloc *Primerbond Roof Restore* on exposed surfaces when rain is anticipated within 5 hours of completion of the work, longer in damp, cold +/- humid conditions
- Avoid application on hot surfaces or in hot &/or windy conditions.
- Application should be carried out on a day with temperatures above 10°C and below 32°C
- Coated area must be protected from damage until the completion of the project; finished work must be protected from rain, frost and severe weather conditions until fully dried

OTHER CONSIDERATIONS**Clean-Up**

Clean up with water

Shelf-Life – Unopened Containers

Maximum two (2) years from date of manufacture when stored correctly.

Transport & Storage

Pails should not be stacked more than three (3) high during transportation and must be transported upright

Store in a cool place, upright, out of direct sunlight and above 4°C

For further information refer to **Safety Data Sheet (SDS)** for Acryloc *Primerbond Roof Restore*

Colorbond® is a trademark of Bluescope Steel Ltd

TECHNICAL DATA

APPEARANCE	Milky white liquid		
ODOUR	Low		
APPLICATION METHODS	Roller, brush, spray		
SPECIFIC GRAVITY (NOMINAL)	~1.03		
THEORETICAL COVERAGE	12-14m ² /L per coat on roofs, 12.5-16.5 m ² /L per coat on masonry		
DRY TIME (25°C & 50% RH) (APPROX)	Tack Free	Recoat/ Overcoat	Fully Dried
	30 mins	After 45	2 hours
NO. OF COATS	Typically 1 coat		

SAFETY & HANDLING

For further information refer to **Safety Data Sheet (SDS)** for Acryloc *Primerbond Roof Restore*, call the Acryloc Tech – **Info line** on 1300 661 745 or visit www.acryloc.com.au

When working with Acryloc *Primerbond Roof Restore* observe the usual precautions for handling acrylic water based products including:

- Avoid inhalation of the vapour, prolonged skin contact and particularly eye contact
- Wear protective clothing to minimize skin contact and wear goggles where splatter is likely
- Where spills occur, soak up liquid spillage with sand/sawdust and dispose of in a sensible manner. Do not permit run-off to sewer, storm water or open bodies of water

Full pails are HEAVY. Wear protective footwear and seek assistance if necessary.

FIRST AID MEASURES

For further information refer to **Safety Data Sheet (SDS)** for Acryloc *Primerbond Roof Restore*, call the Acryloc Tech – **Info line** on 1300 661 745 or visit www.acryloc.com.au

Ingestion

If swallowed, wash out mouth with water. Do **NOT** induce vomiting. Drink at least two (2) glasses of water. Seek medical attention.

Eye

Wash with copious amount of water for 15 minutes holding eyelid(s) open. Take care not to rinse contaminated water into non-affected eye. Seek medical attention.

Advice to Doctor

Treat symptomatically

MANUFACTURED BY:

Bizfine Pty Ltd

T/A Acryloc Building Products

174 Cavan Rd

DRY CREEK

South Australia 5094

P: +61 8 8368 0222 E: sales@acryloc.com.au

F: +61 8 8368 0223 W: www.acryloc.com.au

