

ACRYLOC® ULTRA PSU

PRODUCT TYPE	PACKAGING	NOMINAL WEIGHT
Ultra Interiors	1L, 2L, 4L, 10L Steel Cans, 15L Plastic Pail	1.5kg, 2.9kg, 5.6kg, 14kg, 21kg respectively

DESCRIPTION

Acryloc® *Ultra PSU* (Primer, Sealer, Undercoat) is a superior quality, Low Odour interior primer, highly recommended for interior walls and ceilings throughout the home, office or workspace.

Easy application, fast drying and outstanding sandability result in a smooth finish every time, ready for top coating.

Acryloc *Ultra PSU* is suitable for most internal surfaces including hard plaster, MDF, fibrous-cement sheet, masonry, paper faced plasterboard, wood & ceilings including areas normally susceptible to mould/mildew.

FEATURES & BENEFITS

- Excellent adhesion
 - High hiding power
 - Easy to apply, low spatter formula
 - Water based, Easy & safe clean up
 - Sandable after 90-120 minutes
 - Can be tinted to light/pastel colours
 - Low Odour
-

SUBSTRATE PREPARATION - paint will not adhere to a surface that is dirty.

- Areas not to be coated should be masked and protected

New Unpainted Surfaces

Fill nail holes, cracks and imperfections with an appropriate patching material and sand smooth.

Remove dust and make sure that the surface is clean, sound and free from contaminants such as oil, mould release, silicone, grease and efflorescence.

Previously painted surfaces

Wash down with sugar soap and rinse with clean water.

Check for soundness of the original coating, remove any loose or flaking paint, fill holes and cracks and sand to an even finish.

Gloss or Semi-Gloss finishes must be completely dulled by sanding.

APPLICATION

- Mix thoroughly and check that the colour (if tinted) is correct before commencing work.

Method

- Apply 1 full even coat by brush, spray or roller.
- For Roller application, a medium nap (12mm) roller is recommended; use a larger nap (25mm on rough surfaces). High quality synthetic rollers give best performance. Use a 13 or 15 thou spray tip with Airless spray.

Important Notes

- Care should be taken to keep Acryloc *Ultra PSU* off windows and adjacent surfaces that are not to be coated.
- Application should be carried out on a day with temperatures above 10°C and below 32°C.
- *Ultra PSU* is not recommended for exterior use

Clean-Up

- Clean up with water
-

OTHER CONSIDERATIONS**Shelf-Life – Unopened Containers**

Maximum two (2) years from date of manufacture when stored correctly

Transport & Storage

Pails should not be stacked more than three (3) high during transportation and must be transported upright

Store in a cool place, upright, out of direct sunlight and above 4°C

For further information refer to **MSDS** for Acryloc *Ultra PSU*

TECHNICAL DATA

APPEARANCE	Viscous white liquid			
ODOUR	Low			
APPLICATION METHODS	Roller, brush, spray			
SPECIFIC GRAVITY (NOMINAL)	1.3			
THEORETICAL COVERAGE	10-15 m ² /L per coat			
DRY TIME (25°C & 50% RH) (APPROX)	Tack Free	Sand Back	Recoat/ Overcoat	Fully Dried
	1 hour	90-120 min	2 hours	48 hours
NO. OF COATS	1 coat is recommended			
GLOSS LEVEL	Flat			

SAFETY & HANDLING

Refer to **MSDS** for **Acryloc Ultra PSU** before use. For further information on Material Safety Data Sheets, call the Acryloc Tech – Info line on 1300 661 745 or visit www.acryloc.com.au

When working with **Acryloc Ultra PSU** observe the usual precautions for handling acrylic water based products including:

- Avoid inhalation of the vapour, prolonged skin contact and particularly eye contact
- Wear protective clothing to minimize skin contact and wear goggles where splatter is likely
- Where spills occur, soak up liquid spillage with sand/sawdust and dispose of in a sensible manner. Do not permit run-off to sewer, storm water or open bodies of water

Full pails are HEAVY. Wear protective footwear and seek assistance if necessary.

FIRST AID MEASURES

Refer to **MSDS** for **Acryloc Ultra PSU** before use. For further information on Material Safety Data Sheets, call the Acryloc Tech – Info line on 1300 661 745 or visit www.acryloc.com.au

If swallowed, wash out mouth with water. Do **NOT** induce vomiting. Drink at least two (2) glasses of water. Seek medical attention.

Eye

Wash with copious amount of water for 15 minutes holding eyelid(s) open. Take care not to rinse contaminated water into non-affected eye. Seek medical attention.

Advice to Doctor

Treat symptomatically

MANUFACTURED BY:

Bizfine Pty Ltd

T/A Acryloc Building Products

174 Cavan Rd

DRY CREEK

South Australia 5094

P: +61 8 8368 0222

F: +61 8 8368 0223

E: sales@acryloc.com.au

W: www.acryloc.com.au

