

ACRYLOC® PRIMERBOND™ GRIP COAT

PRODUCT TYPE

Primers

PACKAGING

15L Heavy Duty Plastic Pail

NOMINAL WEIGHT

20kg

DESCRIPTION

Acryloc *Primerbond Grip Coat* is a pigmented masonry primer and sealer with addition of fine grit.

Primerbond Grip Coat is highly penetrative into both dense and porous substrates and performs all of the normal functions of a masonry primer. The fine grit addition provides a mechanical key for a subsequent texture coat, making it much easier to coat smooth surfaces such as tilt-up concrete, fibre cement and similar substrates.

Acryloc *Primerbond Grip Coat* is available in tint bases which allows tinting to a wide range of colours. This helps with opacity of subsequent coats and makes *Primerbond Grip Coat* ideal for use under scratch textures as the tinting helps to hide the substrate.

FEATURES & BENEFITS

- Excellent vapour permeability
- High Penetration
- Strong adhesion
- Alkali resistant, helps block efflorescence
- Easy to apply
- Water based , easy & safe clean up

SUITABLE SUBSTRATES

- Cement Render & other rendered surfaces
- Fibre Cement Sheeting (Fibro/Blue board)
- Clay and Concrete Brickwork
- Concrete blocks
- AAC (Autoclaved Aerated Concrete)
- Tilt Panel & Off form Concrete

SUBSTRATE PREPARATION

- Areas not to be coated should be masked and protected
- All surfaces to be coated must be clean, sound, free from contaminants including; oil, mould release, dust, dirt, silicone, mud, grease, salt, efflorescence, animal droppings and any loose or flaking material
- Care should be taken to keep Acryloc *Primerbond Grip Coat* off windows and adjacent surfaces that are not to be coated, as it can be very difficult to remove once allowed to dry.

APPLICATION

Acryloc *Primerbond Grip Coat* does not require thinning or dilution

Method

- Acryloc *Primerbond Grip Coat* can be applied using a roller, brush, HVLP spray equipment or airless spray
- If using airless spray equipment, a 19 thou tip and white gun filter is recommended
- Apply Acryloc *Primerbond Grip Coat* at the rate of 9-11 m²/L
- Acryloc *Primerbond Grip Coat* must be over-coated with appropriate products from the coating system being used

Important Notes

- Do not apply Acryloc *Primerbond Grip Coat* on exposed surfaces when rain is anticipated within 6 hours of completion work for the days, longer in damp, cold +/- humid conditions
- Avoid application in full sun, on hot surfaces or in hot windy conditions
- Do not apply if Relative Humidity is above 85% or temperature is within 3°C of Dew Point
- Application should be carried out on a day with temperatures above 10°C and below 32°C ambient.
- Surface temperature must be above 10°C during the application and the drying period
- Coated area must be protected from damage until the completion of the project; finished work must be protected from rain, frost, dew and severe weather conditions until fully dried or for at least 48 hours
- Surface to be primed must have a residual moisture content <10%. Moisture meters should be used

OTHER CONSIDERATIONS**Clean-Up**

Clean up with water

Shelf-Life – Unopened Containers

Maximum two (2) years from date of manufacture when stored correctly.

Transport & Storage

Pails should not be stacked more than three (3) high during transportation and must be transported upright

Store in a cool place, upright, out of direct sunlight and above 4°C

For further information refer to **SDS** for *Acryloc Primerbond Grip Coat*

TECHNICAL DATA

APPEARANCE	White viscous liquid	
ODOUR	Low	
APPLICATION METHODS	Roller, brush, spray	
SPECIFIC GRAVITY (NOMINAL)	~ 1.3	
THEORETICAL COVERAGE	9-11 m ² /L	
DRY TIME (25°C & 50% RH) (APPROX)	Tack Free	Recoat/ Overcoat
	30mins -1Hour	After 2 Hours
NO. OF COATS	Typically 1 coat	

SAFETY & HANDLING

Refer to **SDS** for *Acryloc Primerbond Grip Coat* before use. For further information on Material Safety Data Sheets, call the Acryloc Tech – Info line on **1300 661 745** or visit www.acryloc.com.au

When working with *Acryloc Primerbond Grip Coat* observe the usual precautions for handling acrylic water based products including:

- Avoid inhalation of the vapour, prolonged skin contact and particularly eye contact
- Wear protective clothing to minimize skin contact and wear goggles where splatter is likely
- Where spills occur, soak up liquid spillage with sand/sawdust and dispose of in a sensible manner. Do not permit run-off to sewer, storm water or open bodies of water

Full pails are HEAVY. Wear protective footwear and seek assistance if necessary.

FIRST AID MEASURES

Refer to **SDS** for *Acryloc Primerbond Grip Coat* before use. For further information on Material Safety Data Sheets, call the Acryloc Tech – Info line on **1300 661 745** or visit www.acryloc.com.au

Ingestion

If swallowed, wash out mouth with water. Do **NOT** induce vomiting. Drink at least two (2) glasses of water. Seek medical attention.

Eye

Wash with copious amount of water for 15 minutes holding eyelid(s) open. Take care not to rinse contaminated water into non-affected eye. Seek medical attention.

Advice to Doctor

Treat symptomatically

MANUFACTURED BY:

Bizfine Pty Ltd

T/A Acryloc Building Products

174 Cavan Rd

DRY CREEK

South Australia 5094

P: +61 8 8368 0222

E: sales@acryloc.com.au

F: +61 8 8368 0223

W: www.acryloc.com.au