

ACRYLOC® ROLL ON TEXTURES

PRODUCT TYPE

Texture Coats

PACKAGING

4L Steel Can, 15L Heavy Duty Plastic Pail

NOMINAL WEIGHT

7kg, 21kg respectively

DESCRIPTION

Forming part of the Wallcote system, Acryloc *Roll On Textures* are a range of low to medium profile granular coatings, designed to be applied with a roller. A range of textured effects can be achieved using selected roller covers.

Acryloc *Roll on Textures* are available in three grain sizes coatings, manufactured as tintable, white bases and provide an attractive finish on correctly prepared domestic & commercial, exterior & interior wall surfaces.

FEATURES & BENEFITS

- Excellent water resistance
- Excellent vapour permeability
- Excellent durability
- Strong adhesion
- Low maintenance
- Easy to apply
- Water based, Easy & safe clean up
- Tintable

WALLCOTE
Coating System

Refer to the Wallcote System specification for the substrate being coated and carry out any preparatory steps.

Also see "SUBSTRATE PREPARATION" below.

↳ **Prime** (where required)

Acryloc Primerbond Masonry Concentrate
(or) Acryloc Primerbond Rendercoat

↳ **Texture**

Tuscan Fine / Moroccan Medium / Rustic Coarse

↳ **Protective Colour Coat** (required for full warranty)

Acryloc Armourflex Masonry Matt or Lo Sheen

SUITABLE SUBSTRATES – when properly prepared

- Cement Render
- AAC (Autoclaved Aerated Concrete)
- Fibre Cement Sheeting (Fibro/Blue board)
- Rendered expanded polystyrene
- Clay and Concrete Brickwork
- Concrete blocks
- Tilt panel walls
- Other primed exterior surfaces

SUBSTRATE PREPARATION

- Areas not to be coated should be masked and protected
- All surfaces to be coated must be clean, sound, free from contaminants including: oil, mould release, dust, dirt, silicone, mud, grease, salt, efflorescence, animal droppings and any loose or flaking material
- All substrates other than fresh Acryloc Patch must be primed before the application of

Either

- Use Acryloc Rendercoat and apply a single coat at the rate of 12-14 m²/L.
- Allow 45-60 minutes to dry before commencing the texture coat

Or

- Use diluted Acryloc Primerbond Masonry Concentrate and apply a single coat of at the rate of 13-15 m²/L
- Allow 45 minutes to dry before commencing the texture coat
- (Note: Primerbond Masonry Concentrate is supplied as a concentrate which must be diluted 1:1 before use)

APPLICATION

- Acryloc *Roll on Texture* does not require thinning or dilution.
- In warm conditions, up to 200mL of Acryloc Extenda may be added to a 15L pail, 40mL to a 4L can, to provide longer open time.
- Mix thoroughly with a broad, flat stirrer, using an upward lifting action, or use a power mixer
- Power mixing is recommended as this will enhance the workability and give the best coverage.
- A wet edge should be maintained throughout the application and day joints formed at corners, expansion joints or mouldings where they will not be evident after completion

METHOD

- Apply Acryloc *Roll on Texture* to the surface with a suitable texture roller. Load the roller generously and apply in strips 500mm - 750mm in length.
- Once five (5) or six (6) strips have been applied, roll across to even out the surface
- Finish in one direction for an even texture
- Repeat the above steps, only re-rolling 70-100mm into the previously coated area
- Work quickly and without interruption, laying off from the edge to avoid texture imperfections
- If a small area is missed, it is best to touch up when the area is dry. Running out of material midway through a wall surface should be avoided at all times.
In this event, feather the edge and allow texture to dry, then marry in with new material
- Acryloc *Roll on Texture* should not be extended (spread) too far; otherwise durability and hiding power may suffer.

Important Notes

- Care should be taken to keep Acryloc *Roll on Texture* off windows and adjacent surfaces that are not to be coated, as it can be very difficult to remove once allowed to dry
- Do not apply Acryloc *Roll on Texture* when rain is anticipated within 5 hours of completion of the days work, longer in damp, cold +/- humid conditions
- Avoid application in full sun, on hot surfaces or in hot windy conditions
- Application should be carried out on a day with temperatures above 10°C and below 32°C
- Coated area must be protected from damage until the completion of the project; finished work must be protected from rain, frost and severe weather conditions until fully dried
- Acryloc *Roll on Texture* is normally over coated with Acryloc Armourflex for best colour accuracy, to improve durability and to reduce dirt pickup. This is essential for full system warranty.

Clean-Up

Clean up with water

OTHER CONSIDERATIONS**Shelf-Life – Unopened Containers**

Maximum two (2) years from date of manufacture when stored correctly

Transport & Storage

Pails should not be stacked more than three (3) high during transportation and must be transported upright

Store in a cool place, upright, out of direct sunlight and above 4°C

For further information refer to **MSDS** for Acryloc *Roll on Sand Texture*

TECHNICAL DATA

APPEARANCE	Off white textured viscous liquid		
ODOUR	Low		
APPLICATION METHOD	Roller		
SPECIFIC GRAVITY (NOMINAL)	1.4 -1.6		
THEORETICAL COVERAGE	1.7-2.0m ² /L Tuscan; 1.5-1.8m ² /L Moroccan; 1.3-1.7m ² /L Rustic		
WET FILM THICKNESS (RECOMM)	Product grain size		
DRY TIME (25°C & 50% RH) (APPROX)	Tack Free	Recoat/ Overcoat	Fully Dried
	2 hours	After 3 hours	24 hours
NO. OF COATS	Typically 1 coat		
GLOSS LEVEL	Textured – matt		

SAFETY & HANDLING

Refer to **MSDS** for **Acryloc Roll on Texture** before use. For further information on Material Safety Data Sheets, call the Acryloc Tech – Info line on 1300 661 745 or visit www.wallcote.com.au

When working with **Acryloc Roll on Texture** observe the usual precautions for handling acrylic water based products including:

- Avoid inhalation of the vapour, prolonged skin contact and particularly eye contact
- Wear protective clothing to minimize skin contact and wear goggles where splatter is likely
- Where spills occur, soak up liquid spillage with sand/sawdust and dispose of in a sensible manner. Do not permit run-off to sewer, storm water or open bodies of water

Full pails are HEAVY. Wear protective footwear and seek assistance if necessary.

FIRST AID MEASURES

Refer to **MSDS** for **Acryloc Roll on Texture** before use. For further information on Material Safety Data Sheets, call the Acryloc Tech – Info line on 1300 661 745 or visit www.wallcote.com.au

Ingestion

If swallowed, wash out mouth with water. Do **NOT** induce vomiting. Drink at least two (2) glasses of water. Seek medical attention.

Eye

Wash with copious amount of water for 15 minutes holding eyelid(s) open. Take care not to rinse contaminated water into non-affected eye. Seek medical attention.

Advice to Doctor

Treat symptomatically

MANUFACTURED BY:

Bizfine Pty Ltd

T/A Acryloc Building Products

174 Cavan Rd

DRY CREEK

South Australia 5094

P: +61 8 8368 0222

F: +61 8 8368 0223

E: sales@acryloc.com.au

W: www.acryloc.com.au

