

SAFETY DATA SHEET

PRODUCT: MouldeX® Mouldings



SDS Version: 02

SDS Issue Date: 8-Sep-16

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: **MouldeX® Mouldings**

Product Codes: Various

Product Use: MouldeX® Mouldings are manufactured in many shapes and sizes; they are used for façade decoration of buildings, fences and other structures.

Manufacturer: **Prestige Wall Systems Pty Ltd**

Addresses: 24 Humphries Street 4/1764 Sydney Road
Kilkenny SA 5009 Campbellwell VIC 3061
Australia Australia

Emergency Phone: 03 9357 6659

Phone: 1300 663 118

Fax: 1300 676 233

Section 2: HAZARDS IDENTIFICATION

Emergency Overview: Not classified as hazardous, according to the criteria of Safe Work Australia.

Not classified as dangerous goods, according to the ADG Code.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

MouldeX® Mouldings consist of a flame retardant modified EPS (Expanded Polystyrene) core, factory coated with a polymer modified cement render, reinforced with alkali resistant fibreglass mesh.

Ingredients:	CAS No.	%wt.
EPS Components		
Pentane	109-66-0	<1.0
Brominated Hydrocarbon Flame Retardant	3194-55-6	<0.5
Polystyrene	9003-53-6	<50
Render Components		
Sand	14808-60-7	50-70
Cement	65997-15-1	5-60
Hydrated Lime	1305-62-0	0-20
Polymer	9036-19-5	5-20
Fibreglass Mesh		3-8

SAFETY DATA SHEET

PRODUCT: MouldeX[®] Mouldings



Section 4: FIRST AID MEASURES

Description of symptoms and necessary first aid measures caused by exposure:	Inhalation:	Dust from high-speed mechanical cutting and fumes from 'melting' of EPS may cause upper respiratory irritation. Remove to fresh air; if breathing difficulties continue, seek medical advice.
	Skin Contact	Potential for skin irritation from cementitious products. Dust or particles on skin should be removed by washing with soap and water.
	Eye Contact	Dust or particles may cause mechanical eye irritation; fumes may also cause irritation. Rinse eyes with clean water; if irritation persists, seek medical advice.
	Ingestion	No ingestion hazards, as biologically inert.

Medical attention and special treatment: Treat symptomatically.

Section 5: FIRE FIGHTING MEASURES

Despite the presence of a flame retardant modifier EPS products are combustible, and will soften and melt when overheated or ignited. When flame retardant modified EPS is exposed directly to a fire source the retardant decomposition products cause flame quenching, so the EPS will not continue to burn when the fire source is removed.

The polymer modified cementitious render is not combustible.

Suitable extinguishing equipment:	Use water fog, carbon dioxide, dry chemical or foam media.
Specific hazards arising from the product:	Molten EPS may drip, causing fire to spread. Incomplete combustion products cause dense, black smoke, which consists of carbon monoxide, carbon dioxide, styrene and trace amounts of other hydrocarbons.

Special protective equipment and precautions for fire fighters:	Use self-contained breathing apparatus and suitable protective clothing, if there is a risk of exposure to smoke or other products of combustion. Decontamination of used PPE is recommended.
-----------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Section 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:	Nil
Environmental precautions:	Nil
Methods and materials for containment and cleaning up:	Wear appropriate PPE when cleaning up off-cuts and collect waste in a suitable container.

SAFETY DATA SHEET

PRODUCT: MouldeX® Mouldings



Section 7: HANDLING AND STORAGE

Precautions for safe handling:	MouldeX® Mouldings are not classified as dangerous goods or hazardous for storage, handling and transport. It is recommended that the product be secured with protectors to avoid damage and accidental loss during transport. Care should also be taken when manually handling the product in windy, or potentially windy conditions.
Conditions for safe storage and any incompatibilities:	Only store on-site quantities that will be installed within a few days, as prolonged exposure to direct sunlight may affect the integrity of the EPS. Furthermore, store the MouldeX® Mouldings away from ponding water and limit exposure to rain or high moisture conditions. Do not store MouldeX® Mouldings near solvents, or where hot-work, naked flames and sparks will likely be produced.

Section 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Control parameters - exposure standards Nil. and biological monitoring:	
Personal protective equipment (PPE):	It is recommended that safety glasses, dust respirator and protective gloves be worn when cutting or sanding.
Hygiene:	Always wash hands with soap and water before eating, drinking, smoking and using the toilet.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Various widths and shapes; up to 2.4m in length.
Bulk Density:	100-150 kg/m ³
% volatiles	0%
Softening temp:	~80°C (EPS)
Melting point:	220-250°C (EPS)
Flash point:	358°C (EPS)
Auto-ignition temp:	471°C (EPS)

Section 10: STABILITY AND REACTIVITY

Reactivity:	Non-reactive.
Chemical stability:	Stable at ambient temperatures.
Conditions to avoid:	Avoid contact with organic solvents, some insecticides and prolonged exposure to sunlight.
Thermal decomposition:	No decomposition if used in ambient conditions.
Hazardous reactions:	Nil, when the product is stored and handled in accordance with this SDS.

Section 11: TOXICOLOGICAL INFORMATION

No adverse health effects expected when the product is handled in accordance with this SDS.

SAFETY DATA SHEET

PRODUCT: MouldeX® Mouldings



Section 12: ECOLOGICAL INFORMATION

Persistence and degradability: All components of MouldeX® Mouldings are not biodegradable and therefore correct containment, collection and disposal of waste is critical.

Other adverse effects: As MouldeX® Mouldings are a lightweight product, wind dispersion is a risk which needs to be managed.

Section 13: DISPOSAL CONSIDERATIONS

Safe handling of waste: Wear appropriate PPE when cleaning up off-cuts and collect waste in a suitable container.

Disposal methods: Dump waste or incinerate in accordance with local or State authority requirements.

Section 14: TRANSPORTATION INFORMATION

MouldeX® Mouldings are not classified as dangerous goods according to the criteria of the relevant road, rail, maritime and air transport regulations and codes.

Section 15: REGULATORY INFORMATION

MouldeX® Mouldings are non-hazardous and are not listed in the Poisons Schedule.

Section 16: ANY OTHER RELEVANT INFORMATION

This SDS has been prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals, published on 22 April 2016, by Safe Work Australia.

Date amended:	7-Sep-16
Key abbreviations:	ADG Code Australian Code for Transport of Dangerous Goods
	CAS Chemical Abstracts Service
	EPS Expanded Polystyrene
	PWS Prestige Wall Systems Pty Ltd
	SDS Safety Data Sheet

Disclaimer:

The information contained herein relates only to the specified product/ materials and is provided as a general reference. PWS believes the data set-forth herein is accurate as at the date of the SDS and is given in good faith. PWS makes no guarantee or warranty and does not assume any liability with respect to the accuracy or completion of such information.