ACRYLOC® WALLCOTE™ SYSTEM SPECIFICATION
TILT UP, PRECAST and OFF FORM CONCRETE

DESCRIPTION

Tilt Up and Precast Concrete panels are common forms of modern concrete construction, normally used for commercial building projects.

The Acryloc Wallcote System provides a textured finish from a three coat system applied to the concrete panels, comprising masonry primer, an acrylic texture coat and a protective colour coat.

A mould release agent or bond breaker is normally used in the manufacture of the panels and this can leave a residue on the concrete surface. The Wallcote System includes Panel Kleen which aids removal of these residues.

WALLCOTE COATING SYSTEM

The Wallcote System components recommended for use on Tilt Up and Precast Concrete are shown below.

Recommended Components	Notes
Prep Coat - Acryloc Panel Kleen (essential where indicated by bead test)	Acryloc Panel Kleen is designed specifically for the removal of mould release agents / oils from concrete surfaces. Apply to surface and remove with a high pressure cleaner.
Primer (essential)	
Acryloc Primerbond Grip Coat	The fine grit provides a mechanical key for a subsequent texture coat, making it easier to coat smooth surfaces.
Texture Coating (choose from)	
Acryloc Marblecote Medium	Trowel On & Finish with a Texture Float
(or) Acryloc Eco-Tex Fine or Medium	Trowel On & Finish with a Texture Float
(or) Acryloc Allegro Medium	Trowel On & Finish with a Texture Float
	All texture coats are tintable to aid Colour Coat coverage
Membrane Coating (for full durability)	
Acryloc Armourflex	Highly Durable, Masonry Matt or Lo Sheen finish, protective Paint coating, tintable to a wide range of colours
(or) Armourflex Extreme	

FEATURES & BENEFITS

- Excellent water resistance with good vapour permeability
- Excellent crack resistance from a flexible acrylic base
- Strong adhesion and Excellent durability
- Easy to apply, Water based for easy & safe clean up
- Low maintenance

IMPORTANT REQUIREMENTS

- Panels must be installed in accordance with the supplier's instructions and/or job specifications and relevant codes.
- Once application of the Wallcote system has occurred, the applicator is taken to have approved the installation and fixing of the panels
- Application methods, processes and finishes should be approved by the client, preferably with the application of a site sample.

The information provided herein is considered correct at the time of publication. It is the responsibility of those using this information to check that it is current prior to specifying or using any of the products or coating systems. Any advice, recommendation or information provided by any of the officers of Acryloc Building Products in relation to goods manufactured by it for their use and application, is given in good faith and is believed by Acryloc Building Products to be appropriate and reliable. However, this advice, recommendation and information is provided without liability or responsibility without excluding or limiting responsibility under relevant Government acts. Acryloc and other marks followed by the symbol ® or ™ are trademarks.

AUSTRALIAN OWNED, AUSTRALIAN MADE AND PROUD OF IT

PREP COAT

It is essential that the surface is clean, sound, dry and free from contaminants and any loose or flaking material. Holes should be filled and damaged areas patched as required.

In particular, the surface must be tested for the presence of mould release agents that will interfere with adhesion. If possible, determine what material was used in the construction of the panels and refer to the technical data from the manufacturer of the product for guidance on rate of oxidation and residue removal.

Oxidation and breakdown of mould release agents can take many months so testing of the panels is strongly recommended. The simplest test is a water splash test:

- Splash an area with water and observe whether the water beads on the surface or soaks in.
- The water should immediately soak in and the surface should darken.
- Any tendency for beading on the surface indicates a greasy, oily residue and requires the use of Acryloc Panel Kleen to prepare the surface. Refer to the Tech Data Sheet for Acryloc Panel Kleen for further information.

PRIMER

The concrete panel must be primed prior to texture coating.

- Use Acryloc Primerbond Grip Coat primer and apply a single coat of at the rate of 9-11 m2/L
- Allow Primer to dry before commencing following coats

TEXTURE COATING

- Apply the selected Acryloc Trowel-On texture and follow the appropriate Tech Data Sheet.
- Application must be carried out in a brisk uniform fashion, terminating only when a whole area or section is completely coated, for example, at an expansion joint or corner.

Do not texture over expansion or control joints.

- Acryloc texture coatings should not be extended (spread) too far; otherwise durability &/or hiding power may suffer.
- Allow minimum 48 hours before commencing the paint coat.
- Coverage depends upon the particle size of the texture coat; Marblecote Medium should give 12-14 m^2/pail. Fine texture will give a little more while coarser materials will cover less area.

MEMBRANE COATING

Painting of texture with Acryloc Armourflex is required to fully protect against water ingress, minimize dirt build up on the surface and to extend the life of the coating system. Refer to the appropriate Tech Data Sheet

- Apply Acryloc Armourflex as detailed in the current version of the Tech Data Sheet. Coverage should be 4-6m2/litre for a single coat over texture & 8-10 m2/litre on a flat surface.
- Armourflex Extreme can be used if a full elastomeric membrane is specified. Armourflex Extreme can increase warranty in certain situations. Coverage should be 3-3.5 m2/litre for a single coat over texture & 6-8 m2/litre on a flat surface
- Acryloc Armourflex may require thinning, depending upon the application method used. Up to 1L of clean water may be added to a 15L pail (~6.5%) without the need to apply any extra coats. Thorough mixing is essential.
- Greater than 10% addition is not recommended in a final coat.

The information provided herein is considered correct at the time of publication. It is the responsibility of those using this information to check that it is current prior to specifying or using any of the products or coating systems. Any advice, recommendation or information provided by any of the officers of Acryloc Building Products in relation to goods manufactured by it for their use and application, is given in good faith and is believed by Acryloc Building Products to be appropriate and reliable. However, this advice, recommendation and information is provided without liability or responsibility without excluding or limiting responsibility under relevant Government acts. Acryloc and other marks followed by the symbol ® or ™ are trademarks.

AUSTRALIAN OWNED, AUSTRALIAN MADE AND PROUD OF IT

Clean-Up
Clean up all Wallcote System materials with water.

WARRANTY

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law and the benefits provided by our warranty are in addition to other rights and remedies available to the consumer under the law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

In addition to these legal requirements, Acryloc Building Products provides a material replacement warranty against peeling or flaking of the full Wallcote™ System caused by any defect in manufacture for a period of ten years when applied correctly by a skilled and experienced applicator in accordance with all current application criteria, including but not limited to, substrate type and preparation, application rates and methods, prevailing weather conditions and protection of finished work.

Acryloc Building Products provides no warranty, expressed or implied, against damage due to movement of the substrate or structure and Acryloc Building Products cannot accept responsibility for variations in colour, strength, appearance or workability resulting from on-site mixing procedures and conditions.

To claim under this warranty, contact us by phone, mail, or through the 'contact us' facility on our website (see the contact information below), and give details of the claim, including your contact details. Proof of purchase is required and we reserve the right to inspect the affected property at our cost.

MANUFACTURED BY

Bizfine Pty Ltd

T/A Acryloc Building Products

174 Cavan Rd DRY CREEK SA 5094

P: +61 8 8368 0222
F: +61 8 8368 0223

E: sales@acryloc.com.au
W: www.acryloc.com.au

The information provided herein is considered correct at the time of publication. It is the responsibility of those using this information to check that it is current prior to specifying or using any of the products or coating systems. Any advice, recommendation or information provided by any of the officers of Acryloc Building Products in relation to goods manufactured by it for their use and application, is given in good faith and is believed by Acryloc Building Products to be appropriate and reliable. However, this advice, recommendation and information is provided without liability or responsibility without excluding or limiting responsibility under relevant Government acts. Acryloc and other marks followed by the symbol ® or ™ are trademarks.

AUSTRALIAN OWNED, AUSTRALIAN MADE AND PROUD OF IT