

## ACRYLOC® PRIMERBOND™ GRIP COAT

### PRODUCT TYPE

Primers

### PACKAGING

15L Heavy Duty Plastic Pail

### NOMINAL WEIGHT

20kg

### DESCRIPTION

Acryloc *Primerbond Grip Coat* is a pigmented masonry primer and sealer with addition of fine grit.

*Primerbond Grip Coat* is highly penetrative into both dense and porous substrates and performs all of the normal functions of a masonry primer. The fine grit addition provides a mechanical key for a subsequent texture coat, making it much easier to coat smooth surfaces such as tilt-up concrete, fibre cement and similar substrates.

Acryloc *Primerbond Grip Coat* is available in tint bases which allows tinting to a wide range of colours. This helps with opacity of subsequent coats and makes *Primerbond Grip Coat* ideal for use under scratch textures as the tinting helps to hide the substrate.

### FEATURES & BENEFITS

- Excellent vapour permeability
- High Penetration
- Strong adhesion
- Alkali resistant
- Easy to apply
- Water based , easy & safe clean up

### SUITABLE SUBSTRATES

- Cement Render & other rendered surfaces
- Fibre Cement Sheeting (Fibro/Blue board)
- Clay and Concrete Brickwork
- Concrete blocks
- AAC (Autoclaved Aerated Concrete)
- Tilt Panel & Off form Concrete

### SUBSTRATE PREPARATION

- Areas not to be coated should be masked and protected
- All surfaces to be coated must be clean, sound, free from contaminants including; oil, mould release, dust, dirt, silicone, mud, grease, salt, efflorescence, animal droppings and any loose or flaking material
- Care should be taken to keep Acryloc *Primerbond Grip Coat* off windows and adjacent surfaces that are not to be coated, as it can be very difficult to remove once allowed to dry.

### APPLICATION

Acryloc *Primerbond Grip Coat* does not require thinning or dilution

#### Method

- Acryloc *Primerbond Grip Coat* can be applied using a roller, brush, spray.
- If using airless spray equipment, a machine suitable for spraying textured products must be used as *Primerbond Grip Coat* contains fine sand.
- Apply Acryloc *Primerbond Grip Coat* at the rate of 9-11 m<sup>2</sup>/L
- Acryloc *Primerbond Grip Coat* must be over-coated with appropriate products from the coating system being used

#### Important Notes

- Do not apply Acryloc *Primerbond Grip Coat* on exposed surfaces when rain is anticipated within 6 hours of completion work for the days, longer in damp, cold +/- humid conditions
- Avoid application in full sun, on hot surfaces or in hot windy conditions
- Do not apply if Relative Humidity is above 85% or temperature is within 3°C of Dew Point
- Application should be carried out on a day with temperatures above 10°C and below 32°C ambient.
- Surface temperature must be above 10°C during the application and the drying period
- Coated area must be protected from damage until the completion of the project; finished work must be protected from rain, frost, dew and severe weather conditions until fully dried or for at least 48 hours
- Surface to be primed must have a residual moisture content <10%. Moisture meters should be used

**OTHER CONSIDERATIONS****Clean-Up**

Clean up with water

**Shelf-Life – Unopened Containers**

Maximum two (2) years from date of manufacture when stored correctly.

**Transport & Storage**

Pails should not be stacked more than three (3) high during transportation and must be transported upright

Store in a cool place, upright, out of direct sunlight and above 4°C

For further information refer to **SDS** for *Acryloc Primerbond Grip Coat*

**TECHNICAL DATA**

APPEARANCE	White viscous liquid	
ODOUR	Low	
APPLICATION METHODS	Roller, brush, specialist spray units only	
SPECIFIC GRAVITY (NOMINAL)	~ 1.3	
THEORETICAL COVERAGE	9-11 m <sup>2</sup> /L	
DRY TIME (25°C & 50% RH) (APPROX)	Tack Free	Recoat/ Overcoat
	30mins -1Hour	After 2 Hours
NO. OF COATS	Typically 1 coat	

**SAFETY & HANDLING**

Refer to **SDS** for *Acryloc Primerbond Grip Coat* before use. For further information on Material Safety Data Sheets, call the Acryloc Tech – Info line on **1300 661 745** or visit [www.acryloc.com.au](http://www.acryloc.com.au)

When working with *Acryloc Primerbond Grip Coat* observe the usual precautions for handling acrylic water based products including:

- Avoid inhalation of the vapour, prolonged skin contact and particularly eye contact
- Wear protective clothing to minimize skin contact and wear goggles where splatter is likely
- Where spills occur, soak up liquid spillage with sand/sawdust and dispose of in a sensible manner. Do not permit run-off to sewer, storm water or open bodies of water

Full pails are HEAVY. Wear protective footwear and seek assistance if necessary.

**FIRST AID MEASURES**

Refer to **SDS** for *Acryloc Primerbond Grip Coat* before use. For further information on Material Safety Data Sheets, call the Acryloc Tech – Info line on **1300 661 745** or visit [www.acryloc.com.au](http://www.acryloc.com.au)

**Ingestion**

If swallowed, wash out mouth with water. Do **NOT** induce vomiting. Drink at least two (2) glasses of water. Seek medical attention.

**Eye**

Wash with copious amount of water for 15 minutes holding eyelid(s) open. Take care not to rinse contaminated water into non-affected eye. Seek medical attention.

**Advice to Doctor**

Treat symptomatically

**MANUFACTURED BY:**

Bizfine Pty Ltd

T/A Acryloc Building Products

174 Cavan Rd

DRY CREEK

South Australia 5094

P: +61 8 8368 0222

E: [sales@acryloc.com.au](mailto:sales@acryloc.com.au)

F: +61 8 8368 0223

W: [www.acryloc.com.au](http://www.acryloc.com.au)