

ACRYLOC® ROOF CLEAN

PRODUCT TYPE	PACKAGING	NOMINAL WEIGHT
Preparation Products	20L Heavy Duty Plastic Pail	22kg

DESCRIPTION

Acryloc *Roof Clean* is a heavy duty, alkaline, detergent based product designed specifically for releasing moss, lichen, and light deposits of grease and oil from various substrates to make subsequent pressure cleaning faster and more effective.

Acryloc *Roof Clean* is recommended for cleaning roof tiles as part of a roof restoration and can be used on cement, fibro cement & terracotta roofing tiles, walls, floors, driveways, paths and ceramic tiles where fungal growth, oil or grease has to be removed. Acryloc *Roof Clean* is supplied in Ready to Use form.

SUITABLE SUBSTRATES

- Roofing tiles
- Driveways & paths
- Ceramic tiles
- Cement Render
- Concrete bricks & blocks
- Clay brick

APPLICATION

When applying Acryloc *Roof Clean* to a roof, it is recommended that Rainwater tanks be disconnected from the guttering system before commencing work. The guttering should remain disconnected until after application of all subsequent coatings and until all residues are washed from the guttering.

Method

- Mix thoroughly with a broad, flat stirrer, using an upward lifting action, or power mixer
- Acryloc *Roof Clean* can be applied using a roller, brush, pad, HVLP spray equipment or airless spray equipment. If applying on roofs, application with a garden type weed sprayer is recommended
- If using airless spray equipment, a 15 thou tip and white gun filter is recommended
- **Indoors and Shaded Areas**
 - Apply Acryloc *Roof Clean* liberally to the surface, agitate with a broom or similar and allow to soak for at least 1-2 hours. Remove by high pressure cleaning followed by hosing with clean water.
- **Roof Areas**
 - Apply Acryloc *Roof Clean* liberally, leave for at least 1-2 hours, then pressure clean
 - For heavy moss growth, apply Acryloc *Roof Clean* late afternoon or evening and allow to 'soak' overnight before pressure cleaning
- Acryloc *Roof Clean* must be completely removed, preferably by pressure cleaning.

Important Notes

- Avoid application on hot surfaces or in hot &/or windy conditions.
- Avoid allowing the material to dry out during the soaking period
- Roof Clean is slippery when wet, do not walk on areas coated with Roof Clean

OTHER CONSIDERATIONS

Shelf-Life – Unopened Containers

Maximum two (2) years from date of manufacture when stored correctly

Transport & Storage

Drums should not be stacked during transportation and must be transported upright

Store in a cool place, upright, out of direct sunlight and above 4°C

Clean-Up

Clean up with water

TECHNICAL DATA

APPEARANCE	Watery liquid
ODOUR	Low
APPLICATION METHODS	Roller, brush, spray
SPECIFIC GRAVITY (NOMINAL)	~1.04
VOLUME SOLIDS (APPROX)	n/a
WEIGHT SOLIDS (APPROX)	n/a
THEORETICAL COVERAGE	10-15m ² /L per coat
NO. OF COATS	As required, typically 1 coat
SOLVENT FOR CLEANING	Water
FLAMMABILITY	Non-flammable

SAFETY & HANDLING

Refer to **SDS** for **Acryloc Roof Clean** before use. For further information on Safety Data Sheets, call the Acryloc Tech – Info line on **1300 661 745** or visit **www.acryloc.com.au**

Acryloc Roof Clean is alkaline and will cause severe eye irritation. Contact with skin may result in irritation. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

When working with **Acryloc Roof Clean** observe the following precautions as a minimum:

- Avoid prolonged skin contact and particularly eye contact
- Wear rubber or PVC gloves and protective clothing to minimize skin contact
- Wear safety glasses with side shields to protect eyes from splatter
- Where spills occur, soak up liquid spillage with sand/sawdust and dispose of in a sensible manner. Do not permit run-off to sewer, storm water or open bodies of water

**FIRST AID MEASURES**

Refer to **SDS** for **Acryloc Roof Clean** before use. For further information on Safety Data Sheets, call the Acryloc Tech – Info line on **1300 661 745** or visit **www.acryloc.com.au**

Ingestion

If swallowed, immediately wash out mouth with water. Do **NOT** induce vomiting. Drink at least two (2) glasses of water. Seek urgent medical attention.

Eye

Hold eyelids apart and flush eye continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Seek urgent medical attention.

Take care not to rinse contaminated water into non-affected eye.

Skin

If skin contact occurs, remove contaminated clothing and flush skin and hair with running water.

Do not re-use contaminated clothing until washed. Seek medical attention.

Advice to Doctor

Product is a solution of surface active agents and alkali builders in aqueous solution. Treat symptomatically

MANUFACTURED BY:

Bizfine Pty Ltd T/A Acryloc Building Products

174 Cavan Rd
 DRY CREEK
 South Australia 5094

P: +61 8 8368 0222 or 1300 661 745

E: sales@acryloc.com.au

W: www.acryloc.com.au