

ACRYLOC® PRIMERBOND WALL/BOARD SEALER

PRODUCT TYPE	PACKAGING	NOMINAL WEIGHT
Primers & Undercoats	4L, 10L Steel Cans, 15L Plastic Pail	5.6kg, 14kg, 21kg respectively

DESCRIPTION

Acryloc® Primerbond Wall / Board Sealer is a premium water based undercoat wall and board sealer with superior hiding power, suitable for interior and exterior use.

Acryloc Primerbond Wall / Board Sealer is recommended for sealing and undercoating gypsum plaster such as Thistle Multifinish, Gyppine Multifinish or USG Diamond Veneer, MDF, fibrous-cement sheet, masonry and paper faced plasterboard. **Note: Do not use Acryloc Primerbond Wall / Board Sealer on unprimed exterior timber.**

FEATURES & BENEFITS

- Excellent adhesion
- High hiding power
- Easy to apply, fast drying
- Can be tinted to light/pastel colours
- Low Odour
- Water based, Easy & safe clean up

SUBSTRATE PREPARATION - paint will not adhere to a surface that is dirty.

- Areas not to be coated should be masked and protected
- Fill nail holes, cracks and imperfections with an appropriate patching material and sand smooth.
Remove dust and make sure that the surface is clean, sound and free from contaminants such as oil, mould release, silicone, grease and efflorescence.

APPLICATION

- Mix thoroughly and check that the colour (if tinted) is correct before commencing work.

Method

- Apply 1 full even coat by brush, spray or roller.
- For Roller application, a medium nap (12mm) roller is recommended. High quality synthetic rollers give best performance.
- Use a 13 or 15 thou spray tip with Airless spray.
- Allow to dry and sand smooth if required
- A second coat may be required for complete coverage on dark or porous surfaces

Important Notes

- Care should be taken to keep Acryloc Primerbond Wall / Board Sealer off windows and adjacent surfaces that are not to be coated.
- Application should be carried out on a day with temperatures above 10°C and below 32°C.
- If applied to Gypsum Plaster, the surface must not be Drummy, Powdery, Soft, Cracking or contain Efflorescence. These defects must be rectified before application of the coating system.
- The moisture content of the substrate must be less than 15% and pH level less than 10%

Clean-Up

- Clean up with water

OTHER CONSIDERATIONS

Shelf-Life – Unopened Containers - Maximum two (2) years from date of manufacture when stored correctly

building products

Transport & Storage

- Pails should not be stacked more than three (3) high during transportation and must be transported upright
- Store in a cool place, upright, out of direct sunlight and above 4°C
- For further information refer to SDS for Acryloc Primerbond Wall / Board Sealer

TECHNICAL DATA

APPEARANCE	Viscous white liquid			
ODOUR	Low			
APPLICATION METHODS	Roller, brush, spray			
SPECIFIC GRAVITY (NOMINAL)	~1.3			
THEORETICAL COVERAGE	12-16 m ² /L per coat			
DRY TIME (25°C & 50% RH) (APPROX)	Tack Free	Sand Back	Recoat/ Overcoat	Fully Dried
	~ 60 min	90 -100 min	2 hours	48 hours
NO. OF COATS	1 coat is recommended			
GLOSS LEVEL	Flat			

SAFETY & HANDLING

Refer to **SDS for Acryloc Primerbond Wall / Board Sealer** before use. For further information on Material Safety Data Sheets, call the Acryloc **Tech – Info line** on **1300 661 745** or visit **www.acryloc.com.au**

When working with **Acryloc Primerbond Wall / Board Sealer** observe the usual precautions for handling acrylic water based products including:

- Avoid inhalation of the vapour, prolonged skin contact and particularly eye contact
- Wear protective clothing to minimize skin contact and wear goggles where splatter is likely
- Where spills occur, soak up liquid spillage with sand/sawdust and dispose of in a sensible manner. Do not permit run-off to sewer, storm water or open bodies of water

Full pails are HEAVY. Wear protective footwear and seek assistance if necessary.

FIRST AID MEASURES

Refer to **SDS for Acryloc Primerbond Wall / Board Sealer** before use. For further information on Material Safety Data Sheets, call the Acryloc **Tech – Info line** on **1300 661 745** or visit **www.acryloc.com.au**

If swallowed, wash out mouth with water. Do **NOT** induce vomiting. Drink at least two (2) glasses of water. Seek medical attention.

Eye

Wash with copious amount of water for 15 minutes holding eyelid(s) open. Take care not to rinse contaminated water into non-affected eye. Seek medical attention.

Advice to Doctor

Treat symptomatically

MANUFACTURED BY:

Bizfine Pty Ltd

T/A Acryloc Building Products
174 Cavan Rd
DRY CREEK
South Australia 5094

P: +61 8 8368 0222

F: +61 8 8368 0223

E: sales@acryloc.com.au

W: www.acryloc.com.au

