

ACRYLOC® PRIMERBOND ROOF RECOAT

PRODUCT TYPE	PACKAGING	NOMINAL WEIGHT
Primers & Undercoats	15L Heavy Duty Plastic Pail	17kg

DESCRIPTION

Acryloc *Primerbond Roof Recoat* is a pigmented, ready to use, binding primer.

Acryloc *Primerbond Roof Recoat* is the recommended primer for previously painted and aged Colorbond roofs as part of the Roofcote System.

The formulation is designed to bind to the surface and provide a 'key' for subsequent coats.

Note: the existing coating must be sound and adhering strongly to the substrate. Where this is not the case, the existing coating must be completely removed before proceeding.

Acryloc *Primerbond Roof Recoat* is not able to rectify cracking, peeling or blistering of the previous coating.

FEATURES & BENEFITS

- Excellent Binding properties
- Excellent flexibility
- Strong adhesion to previously painted surfaces
- Water based for Easy & Safe clean up

SUITABLE SUBSTRATES

- Previously painted roofs
- Aged (faded) Colorbond roofs

SUBSTRATE PREPARATION

- Areas not to be coated should be masked and protected
- All surfaces to be coated must be clean, sound, free from contaminants including; oil, mould release, dust, dirt, silicone, mud, grease, salt, efflorescence, animal droppings and any loose or flaking material
- Application of Acryloc Mould Rid prior to priming will inhibit growth of moss & lichen.
- Care should be taken to keep Acryloc *Primerbond Roof Recoat* off windows and adjacent surfaces that are not to be coated, as it can be very difficult to remove once allowed to dry

APPLICATION

- Acryloc *Primerbond Roof Recoat* does not require thinning or dilution
- Mix thoroughly with a broad, flat stirrer, using an upward lifting action
- Acryloc *Primerbond Roof Recoat* can be applied using HVLP or airless spray equipment
- If using spray equipment, a 17 or 19 thou tip and white gun filter is recommended
- Apply Acryloc *Primerbond Roof Recoat* liberally, completely covering the surface. Applying excess material is acceptable providing it is not allowed to pool on the surface, as this may affect the top coat.
- *Primerbond Roof Recoat* must be over-coated with an appropriate product from the coating system being used

Important Notes

- Do not apply Acryloc *Primerbond Roof Recoat* on exposed surfaces when rain is anticipated within 5 hours of completion of the work, longer in damp, cold +/- or humid conditions
- Avoid application on hot surfaces or in hot &/or windy conditions.
- Application should be carried out on a day with temperatures above 10°C and below 32°C
- Coated area must be protected from damage until the completion of the project; finished work must be protected from rain, frost and severe weather conditions until fully dried

Clean-Up - Clean up with water

OTHER CONSIDERATIONS

Shelf-Life – Unopened Containers

Maximum two (2) years from date of manufacture when stored correctly.

Transport & Storage

Pails should not be stacked more than three (3) high during transportation and must be transported upright

Store in a cool place, upright, out of direct sunlight and above 4°C

For further information refer to **Safety Data Sheet (SDS)** for Acryloc Primerbond Roof Restore

TECHNICAL DATA

APPEARANCE	Milky white liquid		
ODOUR	Low		
APPLICATION METHODS	Roller, brush, spray		
SPECIFIC GRAVITY (NOMINAL)	~1.1		
THEORETICAL COVERAGE	12-14m ² /L per coat on roofs		
DRY TIME (25°C & 50% RH) (APPROX)	Tack Free	Recoat/ Overcoat	Fully Dried
	60 mins	After 90	N/A
NO. OF COATS	Typically 1 coat		

SAFETY & HANDLING

For further information refer to **Safety Data Sheet (SDS)** for **Acryloc Primerbond Roof Recoat**, call the Acryloc Tech – Info line on **1300 661 745** or visit www.acryloc.com.au

Contact with skin may result in irritation. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

Where this material is used in a poorly ventilated area, at elevated temperatures or in confined spaces, vapour may cause irritation to mucous membranes of the respiratory tract, headache and nausea.

When working with **Acryloc Primerbond Roof Recoat** observe the usual precautions for handling acrylic water based products including:

- Avoid inhalation of the vapour, prolonged skin contact and particularly eye contact
- Wear protective clothing to minimize skin contact and wear goggles where splatter is likely
- Where spills occur, soak up liquid spillage with sand/sawdust and dispose of in a sensible manner. Do not permit run-off to sewer, storm water or open bodies of water

Full pails are HEAVY. Wear protective footwear and seek assistance if necessary.

FIRST AID MEASURES

For further information refer to **Safety Data Sheet (SDS)** for **Acryloc Primerbond Roof Recoat** before use. For further information on Material Safety Data Sheets, call the Acryloc Tech – Info line on **1300 661 745** or visit www.acryloc.com.au

Ingestion

If swallowed, wash out mouth with water. Do **NOT** induce vomiting. Drink at least two (2) glasses of water. Seek medical attention.

Eye

Wash with copious amount of water for 15 minutes holding eyelid(s) open. Take care not to rinse contaminated water into non-affected eye. Seek medical attention.

Advice to Doctor

Treat symptomatically

MANUFACTURED BY:

Bizfine Pty Ltd T/A Acryloc Building Products

174 Cavan Rd

DRY CREEK South Australia 5094

P: +61 8 8368 0222 or 1300 661 745

E: sales@acryloc.com.au

W: www.acryloc.com.au